

Salt System Pro Supplies Kit #KT1012 Quick-Start Guide

1. Start with a clean hot tub, and new or clean filter cartridge(s).
2. Install chlorine generator per the manufacturer's instructions.
3. Fill spa with fresh water and operate circulating pump.
4. Slowly add one bag (53 oz.) of Nexa Dead Sea Minerals per 250 gallons. Always allow minerals to dissolve before operating the chlorine generator.
5. Test water for Alkalinity and pH with Chlorine 4-in-1 test strips; adjust if necessary using Alkalinity Increaser or pH Decrease. Total Alkalinity should be 80-120 ppm and pH between 7.2-7.6. Read all package instructions for more information. Recheck weekly.
6. Check water with Hardness Test Strips: If below 150 ppm, add Increase Calcium to attain a hardness range between 150 - 300 ppm.
7. Add Sea Klear Natural Clarifier at the rate of 1 oz./500 gallons weekly.
8. Add Metal Free stain/metal/scale preventer per label directions.
9. Add Oxy-Spa non-chlorine MPS shock at the rate of 1 1/2 - 2 oz. per 500 gallons at startup and after each use. (1 1/2 tablespoons = approx. 2 oz.)
10. Keep ZorbO in spa to absorb oil scum (replace every 3-6 months).
11. Allow water to circulate to equilibrate spa chemicals for an hour or two (or overnight) then retest with test strips; readjust water balance if necessary.
12. To achieve maximum water disinfection, adjust the run time of the chlorine generator so that free chlorine is maintained between 1.0—3.0 ppm. Test with Chlorine Test Strips weekly. Multiple run times per day is best.
13. Maintain salinity level (approx. 1500 ppm for Nexa Spa) and test weekly with Salt Test Strips. Replenishing Dead Sea Minerals is necessary as water splash out is replaced with fresh water.

CHLORINATOR CELL CLEANING:

The generator cell should be visually checked for scale buildup several times per month and cleaned as needed in a diluted 10% muriatic acid solution, per the manufacturer's instructions. Acid Magic is a safer form of muriatic acid for periodic cell cleaning.

NOTES:

- Read your chlorine generator operator's manual first, and follow all directions.
- Allow at least 24 hours after startup for generator to achieve desired chlorine level.
- Always apply chemicals separately. Read all package directions for additional information.
- Drain spa, clean filters and repeat startup procedure every 2 to 4 months, depending on bather load.

Reorder list:

Nexa Dead Sea Minerals #CA1111	Oxy Spa #CA1021
Alkalinity Up #CA1017	pH Decrease #CA1018
Increase Calcium #CA1020	Metal Free scale preventer #CA1064
Sea Klear Clarifier #CA1013	Chlorine 4-Way Test Strips #TB1003
Salt Test Strips #TB1026	Hardness Test Strips #TB1004
Acid Magic #CA1062	ZorbO Oil Scum Absorber #MT1052